

SID XPRESS

Datasheet



Parameters

SID XPRESS 320-8H

Printhead	SEIKO • 510 nozzles • 50 picoliters
Number of printheads	8 printheads
Resolution	Up to 720 dpi
Ink	● Type Solvent or Eco Solvent
	● Colors CMYK
	● Capacity Main tanks: 1 or 5 liters per color + flush
	● Max. printing width 126" (3,200 mm)
Media	● Feeding System Roll or sheet (max. media weight: 264 lbs - 120 kg)
	● Types Vinyl, perforated vinyl, polyester, banner or canvas
Print Speed	up to 2,818 sq.ft./h (262 m ² /h) • 1 pass 1,689 sq.ft./h (157 m ² /h) • 2 passes 980 sq.ft./h (91 m ² /h) • 3 passes 753 sq.ft./h (70 m ² /h) • 4 passes 495 sq.ft./h (53 m ² /h) • 6 passes
Cleaning System	Automatic Individual Positive Pressure System
Heating and Cooling System	Preheater, platform heater, front heater, two front infrared heaters and a powerful fan system
Interface	USB 2.0
Noise Level	Printing: < 70 dB • Standby: < 40 dB
RIP Software	Photo PRINT 10
Voltage	AC 220 V, 50 Hz / 60 Hz
Power Consumption	7,560 W • 35 A
Operational Temperature	Temperature 68 - 82°F (20 - 28°C) Humidity 40% - 60%, non-condensing
Equipment dimensions (Length x Width x Height)	200" x 41" x 66" (5,080 x 1,040 x 1,670 mm)
Package dimensions (Length x Width x Height)	207" x 48" x 77" (5,250 x 1,210 x 1,950 mm)
Equipment weight	Net Weight 2,013 lbs (913 kg) Gross Weight 2,866 lbs (1300 kg)